

# Intara SQ 175

Article number: 51340005

## LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | BeColor  |
| Luminous flux        | 3490 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 85 lm/W  |
| Reflector            | WallBeam |
| Controller           | On/Off   |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | 30°         |
| Weight                    | 1.8 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | black       |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire mit LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, swivel angle 30°, luminaire housing sheet steel, powder-coated, black, separate driver unit

76500037 driver unit, On/Off, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI, 220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

