

Intara SQ 175

Article number: 51310006

LIGHT TECHNOLOGY


LED	COB
Light colour	835
Luminous flux	7800 lm
System power	59 W
Luminaire Efficiency	132 lm/W
Reflector	BatWing
Beam angle	2 x 25°
Controller	On/Off

LUMINAIRE

Swivel angle	30°
Weight	1.9 kg
Protection rating . class	IP 20 . III
Luminaire colour	silver

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with double asymmetrical light distribution pattern, swivel angle 30° luminaire housing sheet steel, powder-coated, silver, separate driver unit

76500052 driver unit, On/Off, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 18 luminaires per circuit (B16A fuse)

76500116 driver unit, D4i, 220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Ø (m)	E0(0°)(lx)
1.0 m	2.22 2.15 983.0
2.0 m	4.44 4.30 246.0
3.0 m	6.66 6.45 110.0
4.0 m	8.88 8.60 62.0
5.0 m	11.10 10.75 40.0

