

## Pendiro XR

Article number: 80740039

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 2900 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 126 lm/W |
| Reflector            | Medium   |
| Beam angle           | 25°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 1.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 70 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| Height (m) | Beam Diameter (m) | Luminous Flux (lm) |
|------------|-------------------|--------------------|
| 1.0 m      | 0.44              | 11473.0            |
| 2.0 m      | 0.88              | 2868.2             |
| 3.0 m      | 1.32              | 1274.8             |
| 4.0 m      | 1.76              | 717.1              |
| 5.0 m      | 2.20              | 458.9              |
| Ø (m)      |                   | E0(0°) [lx]        |

