

Pendiro XR

Article number: 80740066

LIGHT TECHNOLOGY



| | |
|----------------------|---------|
| LED | COB |
| Light colour | BeCool |
| Luminous flux | 1970 lm |
| System power | 23 W |
| Luminaire Efficiency | 86 lm/W |
| Reflector | Medium |
| Beam angle | 25° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 1.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, white

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 70 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.44 | 7793.7 |
| 2.0 m | 0.88 | 1948.4 |
| 3.0 m | 1.32 | 866.0 |
| 4.0 m | 1.76 | 487.1 |
| 5.0 m | 2.20 | 311.7 |
| Ø (m) | | E0(0°) [lx] |

