

## Intara TX

Article number: 50810005

### LIGHT TECHNOLOGY

LED	SMD
Light colour	835
Luminous flux	10630 lm
System power	72 W
Luminaire Efficiency	148 lm/W
Reflector	WideFlood
Beam angle	60°
Controller	On/Off

### LUMINAIRE

Weight	3.2 kg
Protection rating . class	IP 20 . I
Luminaire colour	white



Lay in luminaire with LED, rated life of the LED L90/B50 50000 h (ambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern (60°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6010 lm), 42 W (6700 lm), 47 W (7380 lm), 52 W (8050 lm), 57 W (8710 lm), 62 W (9360 lm), 67 W (10000 lm), 72 W (10630 lm), 57 Watt preselected, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 16 luminaires per circuit (B16A fuse)

Order accessories separately!

Fastening set for Ceiling Systems with visible supporting profile:

5080Z600 for Ceiling Systems 600, white

5080Z625 for Ceiling Systems 625, white

Cover bracket for Ceiling systems:

5080C600 for Ceiling Systems 600, white

5080C625 for Ceiling Systems 625, white

Through-Wiring:

765Y4000 Y-distributor with plug/socket-3 pole, GST 18/3, L= 4000 mm

inclusive driver Unit: 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse)

