

Intara TX

Article number: 50820005

LIGHT TECHNOLOGY

| | |
|----------------------|----------------|
| LED | SMD |
| Light colour | 835 |
| Luminous flux | 10520 lm |
| System power | 72 W |
| Luminaire Efficiency | 146 lm/W |
| Reflector | Xtra WideFlood |
| Beam angle | 90° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.2 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |



Lay in luminaire with LED, rated life of the LED L90/B50 50000 h (ambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern (90°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (5940 lm), 42 W (6630 lm), 47 W (7300 lm), 52 W (7960 lm), 57 W (8610 lm), 62 W (9250 lm), 67 W (9890 lm), 72 W (10520 lm), 57 W preselected, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 16 luminaires per circuit (B16A fuse)

Order accessories separately!

Fastening set for Ceiling Systems with visible supporting profile:

5080Z600 for Ceiling Systems 600, white

5080Z625 for Ceiling Systems 625, white

Cover bracket for Ceiling systems:

5080C600 for Ceiling Systems 600, white

5080C625 for Ceiling Systems 625, white

Through-Wiring:

765Y4000 Y-distributor with plug/socket-3 pole, GST 18/3, L= 4000 mm

inclusive driver Unit: 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

