

Ontero TX

Article number: 21600089

LIGHT TECHNOLOGY

| | |
|----------------------|----------------|
| LED | SMD |
| Light colour | 835 |
| Luminous flux | 5290 lm |
| System power | 38 W |
| Luminaire Efficiency | 139 lm/W |
| Reflector | Xtra WideFlood |
| Beam angle | 90° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|------------|
| Rotation angle | 300° |
| Weight | 1.16 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | white |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern (90°), TIR-lens made of PMMA, luminaire housing sheet steel, powder-coated, white, locking mechanism to aligned in 15° steps, rotation angle 300°, In-Track-Adapter, Casambi, On/Off, 220-240 V~ / 50-60 Hz, max. 64 luminaires per circuit (B16A fuse)

In-Track-Adapter On/Off, 220-240 V~ / 50-60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

