

Ontero TX


Article number: 21370007

LIGHT TECHNOLOGY

LED	SMD
Light colour	830
Luminous flux	10650 lm
System power	72 W
Luminaire Efficiency	148 lm/W
Reflector	Doppelt Asymmetrisch Wide
Beam angle	2 x 25°
Controller	On/Off

LUMINAIRE

Rotation angle	330°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	silver



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with slight horizontal brightening, Combination of asymmetrical PMMA lenses and 60 ° TIR lenses made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6020 lm), 42 W (6710 lm), 47 W (7390 lm), 52 W (8060 lm), 57 W (8720 lm), 62 W (9370 lm), 67 W (10010 lm), 72 W (10650 lm), 57 Watt preselected, rotation angle 330°, On/Off, DIP-Switch, luminaire housing sheet steel, powder-coated, silver, Multiadapter, max. 16 luminaires per circuit (B16A fuse)

inclusive driver Unit: 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

