

## Ontero TX


Article number: 21390004

### LIGHT TECHNOLOGY

|                      |                |
|----------------------|----------------|
| LED                  | SMD            |
| Light colour         | 830            |
| Luminous flux        | 10310 lm       |
| System power         | 72 W           |
| Luminaire Efficiency | 143 lm/W       |
| Reflector            | Xtra WideFlood |
| Beam angle           | 90°            |
| Controller           | On/Off         |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 330°      |
| Weight                    | 3.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), extra wide, homogeneous light distribution pattern (90°), TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (5830 lm), 42 W (6490 lm), 47 W (7150 lm), 52 W (7800 lm), 57 W (8440 lm), 62 W (9070 lm), 67 W (9690 lm), 72 W (10310 lm), 57 W preselected, rotation angle 330°, On/Off, DIP-Switch, luminaire housing sheet steel, powder-coated, white, Multiadapter, max. 16 luminaires per circuit (B16A fuse)

inclusive driver Unit: 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), DIP-Switch 38W-72W (default 53W), temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

