

Ontero TX

Article number: 21400007

LIGHT TECHNOLOGY

| | |
|----------------------|---------------------------|
| LED | SMD |
| Light colour | 830 |
| Luminous flux | 10650 lm |
| System power | 72 W |
| Luminaire Efficiency | 148 lm/W |
| Reflector | Doppelt Asymmetrisch Wide |
| Beam angle | 2 x 25° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Rotation angle | 330° |
| Weight | 3.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | silver |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with slight horizontal brightening, Combination of asymmetrical PMMA lenses and 60 ° TIR lenses made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6020 lm), 42 W (6710 lm), 47 W (7390 lm), 52 W (8060 lm), 57 W (8720 lm), 62 W (9370 lm), 67 W (10010 lm), 72 W (10650 lm), 57 Watt preselected, rotation angle 330°, DALI OT, DIP-Switch, luminaire housing sheet steel, powder-coated, silver, Multiadapter, max. 21 luminaires per circuit (B16A fuse)

inclusiv driver unit: 220-240 V~ / 50-60 Hz, DALI, max. 15 luminaires per circuit (B16A fuse), temperature protection, temperature protection

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

