

Ontero TX

Article number: 21620008

LIGHT TECHNOLOGY

| | |
|----------------------|-----------------------------|
| LED | SMD |
| Light colour | 835 |
| Luminous flux | 10980 lm |
| System power | 72 W |
| Luminaire Efficiency | 153 lm/W |
| Reflector | Doppelt Asymmetrisch Medium |
| Beam angle | 2 x 25° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Rotation angle | 330° |
| Weight | 3.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6210 lm), 42 W (6920 lm), 47 W (7620 lm), 52 W (8310 lm), 57 W (8990 lm), 62W (9660 lm), 67 W (10330 lm), 72 W (10980 lm), 57 Watt preselected, rotation angle 330°,luminaire housing sheet steel, powder-coated, white, Multiadapter

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

