

Ontero TX


Article number: 21650009

LIGHT TECHNOLOGY

| | |
|----------------------|-------------|
| LED | SMD |
| Light colour | 840 |
| Luminous flux | 11540 lm |
| System power | 72 W |
| Luminaire Efficiency | 160 lm/W |
| Reflector | MediumFlood |
| Beam angle | 30° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Rotation angle | 330° |
| Weight | 3.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |



Surface-mounted luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), wide, homogeneous light distribution pattern 30°, TIR-lens made of PMMA, Driver with power selection via DIP switch, 220-240 V~ / 50-60 Hz, temperature protection, 8 possible levels: 38 W (6530 lm), 42 W (7270 lm), 47 W (8010 lm), 52 W (8730 lm), 57 W (9450 lm), 62W (10160 lm), 67 W (10850 lm), 72 W (11540 lm), 57 Watt preselected, rotation angle 330°, luminaire housing sheet steel, powder-coated, white, Multiadapter

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

