

# Pendiro TX


Article number: 80870003

## LIGHT TECHNOLOGY

|                      |                             |
|----------------------|-----------------------------|
| LED                  | SMD                         |
| Light colour         | 840                         |
| Luminous flux        | 5810 lm                     |
| System power         | 38 W                        |
| Luminaire Efficiency | 153 lm/W                    |
| Reflector            | Doppelt Asymmetrisch Medium |
| Beam angle           | 2 x 25°                     |
| Controller           | On/Off                      |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Rotation angle            | 330°        |
| Weight                    | 1.2 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | matt black  |



Suspended luminaire with LED, rated life of the LED L90/B50 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), double asymmetrical light distribution pattern with horizontal brightening, Combination of asymmetrical PMMA lenses and 30 ° TIR lenses made of PMMA, luminaire housing sheet steel, powder-coated, matt black, power supply via suspension cables

Canopy, sheet steel, powder-coated, inkl. SELV-, canopy /supply set (E-set) please order separately

76500127 E-Set for 3-Ph Track, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), black matt

76500128 E-Set with Canopy, On/Off, 220-240 V~ / 50-60 Hz, max. 16 luminaires per circuit (B16A fuse), black matt

76500133 E-Set for 3-Ph Track, Casambi, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), black matt

76500134 E-Set with Canopy, Casambi, 220-240 V~ / 50-60 Hz, max. 15 luminaires per circuit (B16A fuse), black matt

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

