

Intara CX

Article number: 51410001

LIGHT TECHNOLOGY


LED	LED
Light colour	830
Luminous flux	2330 lm
System power	23 W
Luminaire Efficiency	101 lm/W
Reflector	Downlight
Beam angle	60°
Controller	On/Off

LUMINAIRE

Weight	0.67 kg
Protection rating . class	IP 20 . III
Luminaire colour	black

OPTIONAL

Front ring with RAL / NCS, emergency light function for central supply, fire protection cover (up to 34 W), ceiling reinforcing profile for modular ceiling, reduction ring




Recessed downlight with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with homogeneous light distribution pattern, diffuser lens, translucent, darklight reflector, aluminium, metallised, highgloss, luminaire head die-cast aluminium, powder-coated, ; mounting ring die-cast aluminum, front ring and coverblind plastic, black, separate driver unit

76500034 driver unit, On/Off, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI, 220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500122 driver unit, Casambi, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 23 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	1.28	2196.1
2.0 m	2.56	549.0
3.0 m	3.84	244.0
4.0 m	5.12	137.3
5.0 m	6.40	87.8
Ø (m)		E0(0°) [lx]

