

Intara CX

Article number: 51410003

LIGHT TECHNOLOGY

| | |
|----------------------|-----------|
| LED | LED |
| Light colour | 840 |
| Luminous flux | 1720 lm |
| System power | 17 W |
| Luminaire Efficiency | 101 lm/W |
| Reflector | Downlight |
| Beam angle | 60° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-------------|
| Weight | 0.67 kg |
| Protection rating . class | IP 20 . III |
| Luminaire colour | black |

OPTIONAL

Front ring with RAL / NCS, emergency light function for central supply, fire protection cover (up to 34 W), ceiling reinforcing profile for modular ceiling, reduction ring




Recessed downlight with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with homogeneous light distribution pattern, diffuser lens, translucent, darklight reflector, aluminium, metallised, highgloss, luminaire head die-cast aluminium, powder-coated, ; mounting ring die-cast aluminum, front ring and coverblind plastic, black, separate driver unit

76500050 driver unit, On/Off, 220-240 V / 50-60 Hz, 400 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500051 driver unit, DALI, 220-240 V / 50-60 Hz, 400 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500121 driver unit, Casambi, 220-240 V / 50-60 Hz, 400 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 35 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 1.28 | 1621.1 |
| 2.0 m | 2.56 | 405.3 |
| 3.0 m | 3.84 | 180.1 |
| 4.0 m | 5.12 | 101.3 |
| 5.0 m | 6.40 | 64.8 |
| Ø (m) | | E0(0°) [lx] |

