

# Intara RD 165

Article number: 51110112

## LIGHT TECHNOLOGY


|                      |             |
|----------------------|-------------|
| LED                  | COB         |
| Light colour         | SpecialMeat |
| Luminous flux        | 2260 lm     |
| System power         | 41 W        |
| Luminaire Efficiency | 55 lm/W     |
| Reflector            | Spot        |
| Beam angle           | 20°         |
| Controller           | On/Off      |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +/- 25°     |
| Weight                    | 0.9 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | white       |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 82, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +/-25°, luminaire housing sheet steel, powder-coated, white, separate driver unit

76500037 driver unit, On/Off, 220-240 V / 50-60 Hz, 1050 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

76500042 driver unit, DALI, 220-240 V / 50-60 Hz, 1050 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 22 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.31 | 13649.0     |
| 2.0 m | 0.62 | 3412.3      |
| 3.0 m | 0.93 | 1516.6      |
| 4.0 m | 1.24 | 853.1       |
| 5.0 m | 1.55 | 546.0       |
| Ø (m) |      | E0(0°) [lx] |

