

# Intara RD 165

Article number: 51010002

## LIGHT TECHNOLOGY


|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 830       |
| Luminous flux        | 4230 lm   |
| System power         | 34 W      |
| Luminaire Efficiency | 124 lm/W  |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 30° |
| Controller           | On/Off    |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Swivel angle              | +/- 25°     |
| Weight                    | 0.9 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | black       |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



76500076 driver unit, On/Off, 220-240 V / 50-60 Hz, 850 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500077 driver unit, DALI, 220-240 V / 50-60 Hz, 850 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |           |             |
|-------|-----------|-------------|
| 1.0 m | 1.05 0.41 | 6586.8      |
| 2.0 m | 2.10 0.82 | 1646.7      |
| 3.0 m | 3.15 1.22 | 731.9       |
| 4.0 m | 4.20 1.63 | 411.7       |
| 5.0 m | 5.25 2.04 | 263.5       |
| Ø (m) |           | E0(0°) [lx] |

