

Intara RD 190

Article number: 51140006

LIGHT TECHNOLOGY


LED	COB
Light colour	830
Luminous flux	5480 lm
System power	47 W
Luminaire Efficiency	117 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

LUMINAIRE

Rotation angle	170°
Swivel angle	+/- 30°
Weight	1.3 kg
Protection rating . class	IP 20 . III
Luminaire colour	silver

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver




Recessed luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, rotation angle 170°, swivel angle +/-30°, luminaire housing sheet steel, powder-coated, silver, separate driver unit

76500092 driver unit, On/Off, 220-240 V / 50-60 Hz, 1200 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

76500093 driver unit, DALI, 220-240 V / 50-60 Hz, 1200 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 30 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	33095.9
2.0 m	0.62	8274.0
3.0 m	0.93	3677.3
4.0 m	1.24	2068.5
5.0 m	1.55	1323.8
Ø (m)		E0(0°) [lx]

