

## Intara SX


Article number: 51660045

### LIGHT TECHNOLOGY

LED	COB
Light colour	BeNature
Luminous flux	710 lm
System power	23 W
Luminaire Efficiency	31 lm/W
Reflector	WallWash
Controller	On/Off

### LUMINAIRE

Rotation angle	120°
Swivel angle	0°
Weight	0.46 kg
Protection rating . class	IP 20 . II
Luminaire colour	white



Recessed wallwasher with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 95, chromaticity tolerance 2 SDCM (initial), vaporized plastic reflector, microfasetted, patented free-form optics with asymmetrical light distribution pattern reflector cover made of polycarbonate (PC), high-gloss black, heat sink die-cast aluminium, red anodized, mounting ring die-cast aluminum, white, powder-coated, rotation angle 120°, swivel angle 0° clamp spring for ceiling attachment , including connected driver unit, On/Off, 220-240 V~ / 50-60 Hz, 600 mA, max. 34 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

