

## Intara SX

Article number: 51640012

### LIGHT TECHNOLOGY

LED	COB
Light colour	930
Luminous flux	450 lm
System power	7 W
Luminaire Efficiency	64 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

### LUMINAIRE

Rotation angle	220°
Swivel angle	+/- 20°
Weight	0.45 kg
Protection rating . class	IP 20 . II
Luminaire colour	white



Recessed directional spot with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), vaporized plastic reflector, microfasetted, patented free-form optics with clear and precise light distribution pattern, heat sink die-cast aluminium, red anodized, mounting ring die-cast aluminum, white, powder-coated, rotation angle 220°, swivel angle +/- 20° clamp spring for ceiling attachment , including connected driver unit, On/Off, 220-240 V~ / 50-60 Hz, 150 mA, max. 60 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Inclusiv fix connected driver unit, On/Off 220-240 V~ / 50-60 Hz, max. 60 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

