


Intara XR

Article number: 50880048

LIGHT TECHNOLOGY

LED	COB
Light colour	BeColor
Luminous flux	2660 lm
System power	34 W
Luminaire Efficiency	78 lm/W
Reflector	Medium
Beam angle	24°
Controller	On/Off



LUMINAIRE

Swivel angle	+/- 25°
Weight	0.69 kg
Protection rating . class	IP 20 . II
Luminaire colour	black


Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, black,

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 21 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.45	9220.0
2.0 m	0.90	2305.0
3.0 m	1.35	1024.4
4.0 m	1.80	576.2
5.0 m	2.25	368.8
Ø (m)		E0(0°) [lx]

