BÄRO
Retail
Lighting

# Intara XR

Article number: 50870048

## LIGHT TECHNOLOGY

| | |
|---|---|
| LED | COB |
| Light colour | BeColor |
| Luminous flux | 2690 lm |
| System power | 34 W |
| Luminaire Efficiency | 79 lm/W |
| Reflector | Spot |
| Beam angle | 20° |
| Controller | On/Off |



## LUMINAIRE

| | |
|---|---|
| Swivel angle | +/- 25° |
| Weight | 0.69 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | black |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver

Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, black,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 21 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.