

# Intara XR

Article number: 50880014

## LIGHT TECHNOLOGY

|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeCool  |
| Luminous flux        | 1230 lm |
| System power         | 15 W    |
| Luminaire Efficiency | 82 lm/W |
| Reflector            | Medium  |
| Beam angle           | 24°     |
| Controller           | On/Off  |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Swivel angle              | +/- 25°    |
| Weight                    | 0.69 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | silver     |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle, swivel angle +/- 25°, silver,

Inclusiv fix connected driver unit, 220-240 V~ / 50-60 Hz, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

