

## Intara XR

Article number: 50700026

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 2860 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 124 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 400°       |
| Swivel angle              | +/- 85°    |
| Weight                    | 0.65 kg    |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | white      |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Semi-recessed luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, die-cast aluminium, powder-coated, rotation angle 400°, swivel angle +/- 85°, white, separate driver unit

76500034 driver unit, On/Off, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

76500039 driver unit, DALI, 220-240 V / 50-60 Hz, 600 mA, with GST18/5-pin connector, incl. 5-conductor feed-through wiring, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 24 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.34 | 17402.0     |
| 2.0 m | 0.68 | 4350.5      |
| 3.0 m | 1.02 | 1933.6      |
| 4.0 m | 1.36 | 1087.6      |
| 5.0 m | 1.70 | 696.1       |
| Ø (m) |      | E0(0°) [lx] |

