

# Ontero EC 125

Article number: 21160010

## LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | 830       |
| Luminous flux        | 4970 lm   |
| System power         | 41 W      |
| Luminaire Efficiency | 121 lm/W  |
| Reflector            | OvalBasic |
| Beam angle           | 60° x 40° |
| Controller           | On/Off    |

## LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 350°      |
| Swivel angle              | 210°      |
| Weight                    | 2.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing die-cast aluminium, powder-coated, white, rotation angle 350°, swivel angle 210°, Multiadapter, DALI, max. 20 luminaires per circuit (B16A fuse)

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 20 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

