

# Ontero EC 125

Article number: 21020020

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 3290 lm  |
| System power         | 23 W     |
| Luminaire Efficiency | 143 lm/W |
| Reflector            | Spot     |
| Beam angle           | 20°      |
| Controller           | On/Off   |

## LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 350°      |
| Swivel angle              | 210°      |
| Weight                    | 2.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | silver    |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing die-cast aluminium, powder-coated, silver, rotation angle 350°, swivel angle 210°, Multiadapter, On/Off, max. 34 luminaires per circuit (B16A fuse)

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

