

## Ontero EC 125

Article number: 21360007

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 840      |
| Luminous flux        | 7970 lm  |
| System power         | 59 W     |
| Luminaire Efficiency | 135 lm/W |
| Reflector            | BatWing  |
| Beam angle           | 2 x 25°  |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 350°      |
| Swivel angle              | 210°      |
| Weight                    | 2.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | silver    |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with double asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire housing/head die-cast aluminium, silver, rotation angle 350°, swivel angle 210°, Multiadapter, electronic driver: 220-240 V~ / 50-60 Hz, On/Off, max. 52 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

