

# Ontero IC


Article number: 21840112

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 4640 lm  |
| System power         | 41 W     |
| Luminaire Efficiency | 114 lm/W |
| Reflector            | WallBeam |
| Controller           | On/Off   |

## LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 330°       |
| Swivel angle              | +/- 90°    |
| Weight                    | 1.1 kg     |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | white      |



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with asymmetrical light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head/retention arm die-cast aluminium,, white, rotation angle 330°, swivel angle +/- 90°, In-Track-Adapter (OT), DALI 2, 220-240 V~ / 50-60 Hz, max. 27 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

