

## Ontero IC

Article number: 21520012

### LIGHT TECHNOLOGY


|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 830      |
| Luminous flux        | 2120 lm  |
| System power         | 17 W     |
| Luminaire Efficiency | 125 lm/W |
| Reflector            | Flood    |
| Beam angle           | 40°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |            |
|---------------------------|------------|
| Rotation angle            | 330°       |
| Swivel angle              | +/- 90°    |
| Weight                    | 1.1 kg     |
| Protection rating . class | IP 20 . II |
| Luminaire colour          | silver     |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, changeable reflector, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, primary reflector and kick reflector 99% pure aluminium in MIRO-Silver®, luminaire head/retention arm die-cast aluminium, powder-coated, silver, rotation angle 330°, swivel angle +/- 90°, In-Track-Adapter, Casambi, 220-240 V~ / 50-60 Hz, temperature protection, max. 64 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

