

# Ontero IC

Article number: 21439015

## LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | BeNature |
| Luminous flux        | 750 lm   |
| System power         | 17 W     |
| Luminaire Efficiency | 44 lm/W  |
| Reflector            | Spot     |
| Beam angle           | 20°      |
| Controller           | On/Off   |

## LUMINAIRE

|                           |                |
|---------------------------|----------------|
| Rotation angle            | 330°           |
| Swivel angle              | +/- 90°        |
| Weight                    | 1.1 kg         |
| Protection rating . class | IP 20 . II     |
| Luminaire colour          | special colour |



Surface-mounted luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 95, chromaticity tolerance 2 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, special colour, rotation angle 330°, swivel angle +/- 90°, On/Off, max. 36 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

