

# Ontero ID

Article number: 20630011

## LIGHT TECHNOLOGY

|                      |             |
|----------------------|-------------|
| LED                  | LED         |
| Light colour         | SpecialMeat |
| Luminous flux        | 940 lm      |
| System power         | 17 W        |
| Luminaire Efficiency | 55 lm/W     |
| Reflector            | Medium      |
| Beam angle           | 25°         |
| Controller           | On/Off      |

## LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 330°      |
| Swivel angle              | 90°       |
| Weight                    | 1.3 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

## OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 82, chromaticity tolerance 2 SDCM (initial), 3D silicone lens to reduce the proportion of scattered light, reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 330°, swivel angle 90°, Multiadapter, electronic driver: 220-240 V~ / 50-60 Hz, On/Off, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

