

Ontero SX

Article number: 21700134

LIGHT TECHNOLOGY

| | |
|----------------------|---------|
| LED | COB |
| Light colour | 940 |
| Luminous flux | 1660 lm |
| System power | 23 W |
| Luminaire Efficiency | 72 lm/W |
| Reflector | Flood |
| Beam angle | 40° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|------------|
| Rotation angle | 360° |
| Swivel angle | +/- 90° |
| Weight | 0.58 kg |
| Protection rating . class | IP 20 . II |
| Luminaire colour | black |



Surface-mounted luminaire, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), miniaturized, vaporized plastic reflector, microfasetted, patented free-form optics (Bartenbach®) with clear and precise light distribution pattern, Reflector holder in plastic, black, high-gloss, reflector support ring with threaded connection and air inlet, die-cast aluminum, silver, housing and bracket in die-cast aluminium, powder-coated, Luminaire housing designed as a heat sink, black, Joint cover in housing color with decorative ring, edge area silver, matt (matt gold with Edition) rear perforated sheet metal cover for housing ventilation, rotation angle 360°, swivel angle +/- 90°, inclusive, Casambi, 220-240 V 50/60Hz, 600 mA, max. 64 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

