

Ontero SX

Article number: 21700007

LIGHT TECHNOLOGY

LED	COB
Light colour	930
Luminous flux	1100 lm
System power	17 W
Luminaire Efficiency	65 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

LUMINAIRE

Rotation angle	360°
Swivel angle	+/- 90°
Weight	0.58 kg
Protection rating . class	IP 20 . II
Luminaire colour	white



Surface-mounted luminaire, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), miniaturized, vaporized plastic reflector, microfasetted, patented free-form optics (Bartenbach®) with clear and precise light distribution pattern, Reflector holder in plastic, black, high-gloss, reflector support ring with threaded connection and air inlet, die-cast aluminum, silver, housing and bracket in die-cast aluminium, powder-coated, Luminaire housing designed as a heat sink, white, Joint cover in housing color with decorative ring, edge area silver, matt (matt gold with Edition) rear perforated sheet metal cover for housing ventilation, rotation angle 360°, swivel angle +/- 90°, inclusive, On/Off, 220-240 V 50/60Hz, 400 mA, max. 36 luminaires per circuit (B16A fuse), camera-compatible, up to 2.5 KV interference resistance

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

