

## Ontero XR

Article number: 20830088

### LIGHT TECHNOLOGY

|                      |          |
|----------------------|----------|
| LED                  | COB      |
| Light colour         | 835      |
| Luminous flux        | 3720 lm  |
| System power         | 34 W     |
| Luminaire Efficiency | 109 lm/W |
| Reflector            | Spot     |
| Beam angle           | 15°      |
| Controller           | On/Off   |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Rotation angle            | 400°      |
| Swivel angle              | +/- 85°   |
| Weight                    | 0.69 kg   |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |


### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Surface-mounted luminaire mit LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head/retention arm die-cast aluminium, powder-coated, black, rotation angle 400°, swivel angle +/- 85°, DALI, max. 50 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.34 | 22634.7     |
| 2.0 m | 0.68 | 5658.7      |
| 3.0 m | 1.02 | 2515.0      |
| 4.0 m | 1.36 | 1414.7      |
| 5.0 m | 1.70 | 905.4       |
| Ø (m) |      | E0(0°) [lx] |

