

Pendiro AM 290

Article number: 81230008

LIGHT TECHNOLOGY

LED	COB
Light colour	840
Luminous flux	4690 lm
System power	34 W
Luminaire Efficiency	138 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

LUMINAIRE

Swivel angle	+/- 25°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	silver

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +/-25°, luminaire housing sheet steel, powder-coated, silver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	26392.2
2.0 m	0.62	6598.0
3.0 m	0.93	2932.5
4.0 m	1.24	1649.5
5.0 m	1.55	1055.7
Ø (m)		E0(0°) [lx]

