

## Pendiro AM 290

Article number: 81230003

### LIGHT TECHNOLOGY


LED	COB
Light colour	835
Luminous flux	4260 lm
System power	34 W
Luminaire Efficiency	127 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

### LUMINAIRE

Swivel angle	+/- 25°
Weight	3.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	black

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +/-25°, luminaire housing sheet steel, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.31	25727.8
2.0 m	0.62	6432.0
3.0 m	0.93	2858.6
4.0 m	1.24	1608.0
5.0 m	1.55	1029.1
Ø (m)		E0(0°) [lx]

