

## Pendiro AM 290

Article number: 81210101

### LIGHT TECHNOLOGY

|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | Meat&Fish |
| Luminous flux        | 2420 lm   |
| System power         | 34 W      |
| Luminaire Efficiency | 71 lm/W   |
| Reflector            | Flood     |
| Beam angle           | 40°       |
| Controller           | On/Off    |

### LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Swivel angle              | +/- 25°   |
| Weight                    | 3.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | black     |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +/-25°, luminaire housing sheet steel, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

