

## Pendiro EC 125

Article number: 81020204

### LIGHT TECHNOLOGY

LED	COB
Light colour	840
Luminous flux	5150 lm
System power	41 W
Luminaire Efficiency	126 lm/W
Reflector	Spot
Beam angle	20°
Controller	On/Off

### LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	black

### OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.36	26556.8
2.0 m	0.72	6639.2
3.0 m	1.08	2950.8
4.0 m	1.44	1659.8
5.0 m	1.80	1062.3
Ø (m)		E0(0°) [lx]

