

# Pendiro EC 125

Article number: 81080114

## LIGHT TECHNOLOGY



|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 2620 lm    |
| System power         | 23 W       |
| Luminaire Efficiency | 114 lm/W   |
| Reflector            | Spot       |
| Beam angle           | 20°        |
| Controller           | On/Off     |

## LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 2.7 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | white       |

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 90, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, white, separate driver unit

76500034 driver unit, On/Off, 220-240 V / 50-60 Hz, 600 mA, camera-compatible, up to 2.5 KV interference resistance, SELV, max. 34 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.31 | 15823.2     |
| 2.0 m | 0.62 | 3955.8      |
| 3.0 m | 0.93 | 1758.1      |
| 4.0 m | 1.24 | 989.0       |
| 5.0 m | 1.55 | 632.9       |
| Ø (m) |      | E0(0°) [lx] |

