

Pendiro EC 125

Article number: 81040210

LIGHT TECHNOLOGY



| | |
|----------------------|-----------|
| LED | COB |
| Light colour | 830 |
| Luminous flux | 4970 lm |
| System power | 41 W |
| Luminaire Efficiency | 121 lm/W |
| Reflector | OvalBasic |
| Beam angle | 60° x 40° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 3.0 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, canopy sheet steel, powder-coated, luminaire head die-cast aluminium, powder-coated, white

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|-------------|--------|
| 1.0 m | 1.05 0.41 | 7739.1 |
| 2.0 m | 2.10 0.82 | 1934.8 |
| 3.0 m | 3.15 1.22 | 859.9 |
| 4.0 m | 4.20 1.63 | 483.7 |
| 5.0 m | 5.25 2.04 | 309.6 |
| Ø (m) | E0(0°) [lx] | |

