

Pendiro EC 125

Article number: 81000204

LIGHT TECHNOLOGY


LED	COB
Light colour	840
Luminous flux	5150 lm
System power	41 W
Luminaire Efficiency	126 lm/W
Reflector	Flood
Beam angle	40°
Controller	On/Off

LUMINAIRE

Weight	3.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	black

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, luminaire head die-cast aluminium, powder-coated, black

Multidapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



Height (m)	Beam Diameter (m)	Luminous Flux (lm)
1.0 m	0.77	10853.4
2.0 m	1.54	2713.3
3.0 m	2.31	1205.9
4.0 m	3.08	678.3
5.0 m	3.85	434.1

Ø (m) E0(0°) [lx]

