

## Pendiro IC

Article number: 80680017

### LIGHT TECHNOLOGY


|                      |         |
|----------------------|---------|
| LED                  | COB     |
| Light colour         | BeColor |
| Luminous flux        | 1400 lm |
| System power         | 17 W    |
| Luminaire Efficiency | 82 lm/W |
| Reflector            | Spot    |
| Beam angle           | 20°     |
| Controller           | On/Off  |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 0.8 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | silver      |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 96, chromaticity tolerance 2 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, 3D silicone lens to reduce the proportion of scattered light, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, silver  
Please order canopy and driver unit separatly

Recessed canopy Mounting plate with accessories for recessed fitting, Connecting cable with plug connection for driver unit, cover sheet steel, powder-coated

76500053 Canopy, silver  
76500054 Canopy, black  
76500055 Canopy, white

no text for driver units activated !

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

