

Pendiro ID

Article number: 80660032

LIGHT TECHNOLOGY

Light colour Meat&	Fish
Luminous flux 1090 lr	n
System power 17 W	
Luminaire Efficiency 64 lm/	W
Reflector OvalBa	sic
Beam angle 60° x 4	•0°
Controller On/Off	

LUMINAIRE

Weight Protection rating . class Luminaire colour


OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver

0.7 kg

white

IP 20. III





Suspended luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 70, chromaticity tolerance 2 SDCM (initial), reflector with oval light distribution pattern, 3D silicone lens to reduce the proportion of scattered light, reflector pure aluminium 99,99% in MIRO-Silver®, segmented, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, white

Please order canopy and driver unit separatly

Recessed canopy Mounting plate with accessories for recessed fitting, Connecting cable with plug connection for driver unit, cover sheet steel, powder-coated

76500053 Canopy, silver 76500054 Canopy, black 76500055 Canopy, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

