

## Pendiro ID

Article number: 80640032

### LIGHT TECHNOLOGY


|                      |           |
|----------------------|-----------|
| LED                  | COB       |
| Light colour         | Meat&Fish |
| Luminous flux        | 1540 lm   |
| System power         | 23 W      |
| Luminaire Efficiency | 67 lm/W   |
| Reflector            | Medium    |
| Beam angle           | 25°       |
| Controller           | On/Off    |

### LUMINAIRE

|                           |             |
|---------------------------|-------------|
| Weight                    | 0.7 kg      |
| Protection rating . class | IP 20 . III |
| Luminaire colour          | white       |

### OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 70, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, 3D silicone lens to reduce the proportion of scattered light, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, white  
Please order canopy and driver unit separately

Recessed canopy Mounting plate with accessories for recessed fitting, Connecting cable with plug connection for driver unit, cover sheet steel, powder-coated

76500053 Canopy, silver  
76500054 Canopy, black  
76500055 Canopy, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

