

Pendiro ID

Article number: 80650003

LIGHT TECHNOLOGY



LED	COB
Light colour	840
Luminous flux	3080 lm
System power	23 W
Luminaire Efficiency	134 lm/W
Reflector	Flood
Beam angle	44°
Controller	On/Off

LUMINAIRE

Weight	0.7 kg
Protection rating . class	IP 20 . III
Luminaire colour	black

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 50000 h (tambient 25°C), colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, exchangeable reflector unit in high-sheen black plastic, with glass cover, luminaire housing die-cast aluminium, powder-coated, black
Please order canopy and driver unit separatly

Recessed canopy Mounting plate with accessories for recessed fitting,
Connecting cable with plug
connection for driver unit, cover sheet steel, powder-coated

76500053 Canopy, silver
76500054 Canopy, black
76500055 Canopy, white

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.

