

# Pendiro XR

Article number: 80760008

## LIGHT TECHNOLOGY

LED	COB
Light colour	835
Luminous flux	1380 lm
System power	15 W
Luminaire Efficiency	92 lm/W
Reflector	NarrowSpot
Beam angle	10°
Controller	On/Off

## LUMINAIRE

Weight	1.0 kg
Protection rating . class	IP 20 . I
Luminaire colour	silver

## OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 3 SDCM (initial), rotation-symmetrical reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, silver

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 104 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.18	28024.8
2.0 m	0.36	7006.2
3.0 m	0.54	3113.9
4.0 m	0.72	1751.6
5.0 m	0.90	1121.0
Ø (m)		E0(0°) [lx]

