

Pendiro XR

Article number: 80720016

LIGHT TECHNOLOGY

| | |
|----------------------|------------|
| LED | COB |
| Light colour | 927 |
| Luminous flux | 1040 lm |
| System power | 15 W |
| Luminaire Efficiency | 69 lm/W |
| Reflector | NarrowSpot |
| Beam angle | 10° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Weight | 1.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | white |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 104 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.18 | 21120.2 |
| 2.0 m | 0.36 | 5280.0 |
| 3.0 m | 0.54 | 2346.7 |
| 4.0 m | 0.72 | 1320.0 |
| 5.0 m | 0.90 | 844.8 |
| Ø (m) | | E0(0°) [lx] |

