

Pendiro XR

Article number: 80720021

LIGHT TECHNOLOGY

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | PearlWhite |
| Luminous flux        | 1120 lm    |
| System power         | 15 W       |
| Luminaire Efficiency | 75 lm/W    |
| Reflector            | NarrowSpot |
| Beam angle           | 10°        |
| Controller           | On/Off     |

LUMINAIRE

|                           |           |
|---------------------------|-----------|
| Weight                    | 1.1 kg    |
| Protection rating . class | IP 20 . I |
| Luminaire colour          | white     |

OPTIONAL

RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 104 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



|       |      |             |
|-------|------|-------------|
| 1.0 m | 0.18 | 22744.8     |
| 2.0 m | 0.36 | 5686.2      |
| 3.0 m | 0.54 | 2527.2      |
| 4.0 m | 0.72 | 1421.5      |
| 5.0 m | 0.90 | 909.8       |
| Ø (m) |      | E0(0°) [lx] |

