

Pendiro XR

Article number: 80740003

LIGHT TECHNOLOGY



LED	COB
Light colour	840
Luminous flux	2080 lm
System power	15 W
Luminaire Efficiency	139 lm/W
Reflector	Medium
Beam angle	25°
Controller	On/Off

LUMINAIRE

Weight	1.1 kg
Protection rating . class	IP 20 . I
Luminaire colour	black

OPTIONAL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, segmented and faceted, 3D lens silicon to reduce the proportion of scattered light, luminaire head die-cast aluminium, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, max. 104 luminaires per circuit (B16A fuse)

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



1.0 m	0.44	8228.9
2.0 m	0.88	2057.2
3.0 m	1.32	914.3
4.0 m	1.76	514.3
5.0 m	2.20	329.2
Ø (m)		E0(0°) [lx]

