

Pendiro AM 290

Article number: 81210002

LIGHT TECHNOLOGY


| | |
|----------------------|----------|
| LED | COB |
| Light colour | 830 |
| Luminous flux | 4230 lm |
| System power | 34 W |
| Luminaire Efficiency | 126 lm/W |
| Reflector | Flood |
| Beam angle | 40° |
| Controller | On/Off |

LUMINAIRE

| | |
|---------------------------|-----------|
| Swivel angle | +/- 25° |
| Weight | 3.1 kg |
| Protection rating . class | IP 20 . I |
| Luminaire colour | black |

OPTIONEEL


RAL-colours, NCS-colours (powder coating or wet spraying) on inquiry, surface alloys on inquiry, honeycomb louver



Suspended luminaire with LED, rated life of the LED L80/B10 > 50000 h, colour rendering index CRI > 80, chromaticity tolerance 2 SDCM (initial), reflector with circular light distribution pattern, reflector pure aluminium 99,99% in MIRO-Silver®, swivel angle +/-25°, luminaire housing sheet steel, powder-coated, black

Multiadapter black, inclusive driver unit: 220-240 V~ / 50-60 Hz, 220-240 V, 50/60 Hz

Note: All data are typical values. System features may change with product improvements due to technical advances. Errors excepted.



| | | |
|-------|------|-------------|
| 1.0 m | 0.73 | 8399.1 |
| 2.0 m | 1.46 | 2099.8 |
| 3.0 m | 2.19 | 933.2 |
| 4.0 m | 2.92 | 524.9 |
| 5.0 m | 3.65 | 336.0 |
| Ø (m) | | E0(0°) [lx] |

